

DEC 04 2008

Docket No. F-8993

Ser. No. 10/568,397

**AMENDMENTS TO THE CLAIMS:**

Please replace the claims with the claims provided in the listing below wherein status, amendments, additions and cancellations are indicated.

1-5. (Cancelled)

6. (Currently amended) A method of manufacturing a vehicle's wheel formed of lightweight metal, comprising;

preparing a first forming tool, which has on ~~[[its]]~~ a pressing face thereof, recesses or holes that are arranged in a rotational symmetry of predetermined angle around a center axis, said first forming tool further including an annular recess;

preparing a second forming tool, which has on its pressing face, one or more projections only within a certain angular region about a corresponding center axis;

preparing an intermediate product by casting or forging so as to integrally form at least a center part and a discoid part, which ~~[[are]]~~ respectively corresponding correspond to a hub and a disk of the wheel, said casting or forging further forming a cylindrical tube of thick wall which corresponds to a rim of the wheel, said cylindrical tube of thick wall being integrally formed with said center part and said discoid part of the intermediate product;

heating the intermediate product to a plasticity temperature;

Docket No. F-8993

Ser. No. 10/568,397

placing the intermediate product so as to be held coaxially on the first forming tool, the cylindrical tube being received in said annular recess of the first forming tool;

positioning the second forming tool relative to the first forming tool, so as to be coaxial with the first forming tool and so that each of the projections is positioned to match one of said recesses or holes;

pressing a portion of the discoid part by thrusting the second forming tool relative to the first forming tool as to punch out one or more holes on the portion of the discoid part or to forge the portion of the discoid part;

retreating the second forming tool relative to the first forming tool, after the pressing;

rotating the first forming tool around its center axis by said predetermined angle, relative to the second forming tool, after the retreating; and

repeating the pressing, the retreating and the rotating, until said pressing is made for every one of said recesses or holes on the first forming tool.

7. (Cancelled)

8. (Previously presented) A method of manufacturing a vehicle's wheel according to claim 6, further comprising;

Docket No. F-8993

Ser. No. 10/568,397

preparing a third forming tool which has, on its pressing face, one or more projections only within a certain angular region about a center axis thereof;

positioning the third forming tool relative to the first forming tool, so as to be coaxial with the first forming tool and so that each of the projections is positioned to match an adjacency of one of said recesses or holes;

pressing a portion of the discoid part by thrusting the third forming tool relative to the first forming tool so as to forge said adjacency of one or more of said recesses or holes;

retreating the third forming tool relative to the first form, after the pressing;

rotating the first forming tool around said center axis thereof by said predetermined angle, relative to the third forming tool, after the retreating; and

repeating of the pressing, the retreating and the rotating, until said pressing is made on said each adjacency for every one of said recesses or holes on the first forming tool.

9. (Previously presented) A method of manufacturing a vehicle's wheel according to claim 6, further comprising:

providing waste holes on the discoid part of the intermediate product before said placing, as arranged in a rotational symmetry of said predetermined angle around a center axis of the intermediate product;

Docket No. F-8993

Ser. No. 10/568,397

wherein each of the waste holes is smaller than a corresponding one of said recesses or holes, and is positioned to match the corresponding one of said recesses or holes at a time of said positioning.

10. (Previously presented ) A method of manufacturing a vehicle's wheel according to claim 8, further comprising:

finishing with a fourth forming tool that has projections, each of which corresponds to one of the projections of the third forming tool, so as to finish a pattern of holes on the disk and depressions on a rim of the wheel.

11. (Previously presented) A method of manufacturing a vehicle's wheel according to claim 6, wherein ridges of said projections on the second forming tool, which are for punching the holes on the discoid part, are shaped as sharp-angled in a sectional view along the center axis, at a 90 degree or sharper angle.

12. (Currently amended) A method of manufacturing a vehicle's wheel according to claim 11, wherein a distal end surface of each of said projections is shaped as concave so that said ridges of the projections are shaped as sharp-angled at an angle less than 90 degrees.

13. (Cancelled)